

KEY - FEATURES



Precharged
with R134a
refrigerant



Very robust
structure



Low
maintenance

Main Advantages:

- High performance wall mount HVAC.
- Perfect match for your vehicle – Available in 12V or 24V, suited for different cab types.
- Easy access refrigerant and heater hose connections for improved serviceability.
- Adjustable thermostat and water valve controls

Suggested Applications



www.bergstrominc.com



World Headquarters

Rockford, U.S.A.

+ 1 - 815-874-7821

Europe

Wales, United Kingdom

+ 44 - 144-386-212

Madrid, Spain

+ 34 - 918-775-840

Asia-Pacific

Changzhou, Jiangsu, China

+ 86 - 519-511-7821

BAMS-T-K600-22R2-EN-B

KK-600

Heavy Duty HVAC System



Standalone backwall-mounted HVAC unit

Powered directly by the vehicle battery, KK-600 is the ideal solution when there is not an original HVAC installed or when additional HVAC is required.

Voltage	12V	24V
Cooling capacity (*)	9,8 kW 33,320 BTU/hr	9,8 kW 33,320 BTU/hr
Heating capacity (*)	14,0 kW 47,750 BTU/hr	14,0 kW 47,750 BTU/hr
Elect. consumption	12 A/hr	6 A/hr
Cooling Maximum air flow	552 m³/h 325 SCFM	552 m³/h 325 SCFM
Heating Maximum air flow	637 m³/h 375 SCFM	637 m³/h 375 SCFM
Dimensions	533 x 229 x 813 mm 21 x 9 x 32 in	
Weight	31,8 kg 70 lb	

The cooling capacity was determined in the following conditions:

- inside temperature, 90°F (32°C)/relative humidity 50%
- outside temperature, 100°F (38°C)

Features

- High performance wall mount AC/heater
- Heavy duty steel construction
- 3-speed blower switch
- Adjustable thermostat and water valve controls
- Durable double wheel plastic blower
- (3) 3" Directional top louvers
- (4) Directional front louvers
- Easy access refrigerant and heater hose connections for improved serviceability
- Available in 12 or 24 voltages

ARTICLE No.

12V	24V
HVAC = 1002207730	HVAC = 1002207731

